



AT A GLANCE

High performance subwoofer
Down to 25Hz at -6dB and still 102dB/1W/1m Efficiency
Real 3600W RMS power capacity
Premium 21" LF drivers with massive 115mm long throw
DCS cooling system for low power compression
Heavy braced cabinet for vibration free dynamic response
Textured Waterborne Black coating

APPLICATIONS

CSW221 subwoofer is suitable for bass reinforcement for main PA systems, touring or permanent installations for small to large stages, indoor or outdoor live performances. Suitable in spaces like:

- FoH
- Multi-functional room
- Auditorium and Theatre
- Pub
- Bar
- Night club
- Church

SPECIFICATIONS

Power handling (50~500Hz AES)	3600W RMS / 6000W Program
Nominal impedance	4 Ohm
Frequency response (-6dB half space, no EQ)	28~900Hz
Average Sensitivity in useable band (40~100Hz)	102dB/W/m
Calculated Maximum SPL / 1m	137dB continuous / 143dB Peak
Nominal Directivity (-6dB)	Omni in useable band
Recommended filters	High-pass: 30Hz 24dB/oct Low-pass: 80~110Hz
Low Frequency driver	Custom made 21" CELTO Acoustique Ferrite magnet, 4" ultra long stroke In / Out Voice coil
Crossover	No, active mode only
Flying hardware	No, stack ground use only
Connectors	2x NEUTRIK Speakon® NL4MP (1+/1- Input)
Pole mount	Yes, 2pcs M20 threaded pole
Cabinet	CNC made with tongue and groove assembly 18mm Baltic birch plywood, exterior grade
Finish	Textured Waterborne Black coating
Size (WxHxD)	1226x588x805mm
Weight	99kg net, 115kg gross