



## AT A GLANCE

- Real 120W RMS with high-end sound quality
- Coaxial transducer for unmatched spacial coherence
- Audiophile grade crossover with Right-Phase topology
- Birch plywood cabinet with smooth texture or varnish finish
- Full range with deep and warm bass
- HF compression driver with Ketone Polymer dome
- Multi-functional yoke with dented ring for secured angles
- Available in Black, White, Natural and Oak colors

## SPECIFICATIONS

Power handling (AES Standard)	120W RMS / 480W Peak
Nominal impedance	12 Ohm
Frequency response (-6dB half space, no EQ)	65~22000Hz
Manufacturing Consistency tolerance	±2dB from 300 to 12000Hz
Average Sensitivity (wideband 200~16000Hz)	90dB/W/m
Calculated Maximum SPL / 1m	111dB continuous / 117dB Peak
Nominal Directivity (-6dB)	85° conical above 800Hz
Recommended low cut filter	30Hz 24dB/oct in full range mode 60-140Hz with subwoofer
Low Frequency driver	Custom 6" Coaxial CELTO Acoustique Ferrite magnet, 1.5" Voice coil
High Frequency driver	0.75" exit (Coaxial) 1.1" Ketone olymer diaphragm
Crossover	Passive mode only 2500Hz, 12dB/oct on LF, 18dB/oct on HF
Flying hardware	Integrated Multi-function Yoke
Connectors	Screw terminals with banana plug
Cabinet	CNC made with tongue and grove assembly 12 mm birch plywood
Finish	Smooth textured coating (Black and White colors) or Varnish finish (Natural and Oak colors)
Size (HxWxD)	260x190x250mm
Weight	5.5kg net, 7kg gross