



AT A GLANCE

- Real 200W RMS with high-end sound quality
- Coaxial transducer for unmatched spacial coherence
- Audiophile grade crossover with Right-Phase topology
- Birch plywood cabinet with smooth texture or varnish finish
- Full range with deep and warm bass
- HF compression driver with Ketone Polymer dome
- Multi-functional yoke with dented ring for secured angles
- Available in Black, White, Natural and Oak colors

SPECIFICATIONS

Power handling (AES Standard)	200W RMS / 800W Peak
Nominal impedance	8 Ohm
Frequency response (-6dB half space, no EQ)	52~22000Hz
Manufacturing Consistency tolerance	±2dB from 300 to 12000Hz
Average Sensitivity (wideband 200~16000Hz)	92dB/W/m
Calculated Maximum SPL / 1m	115dB continuous / 121dB Peak
Nominal Directivity (-6dB)	80° conical above 1000Hz
Recommended low cut filter	30Hz 24dB/oct in full range mode 60-140Hz with subwoofer
Low Frequency driver	Custom 7.5" Coaxial CELTO Acoustique Ferrite magnet, 2" Voice coil
High Frequency driver	0.75" exit (Coaxial) 1.1" Ketone Polymer diaphragm
Crossover	Passive mode only 2500Hz, 12dB/oct on LF, 18dB/oct on HF
Flying hardware	Integrated Multi-function Yoke
Connectors	Screw terminals with banana plug
Cabinet	CNC made with tongue and groove assembly 15 mm birch plywood
Finish	Smooth textured coating (Black and White colors) or Varnish finish (Natural and Oak colors)
Size (HxWxD)	246x370x268mm
Weight	8kg net, 11kg gross