

Product Description:

Portable and Installed PA loudspeakers used in applications including sound reinforcement and stage monitoring in Houses of Worship, Events, Clubs, Rehearsal Halls, Ballrooms. Σ Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High SPL and sensitivity
- 1 x 8" high power low frequency transducer
- 1 x 1" PEI diaphragm compression driver
- Passive configuration
- 140° x 140° wide angle coverage pattern
- 1 x NL4 connector
- Computer aided design to optimise frequency and phase response
- Multi purpose cabinet design for FOH or monitor use
- Use as a main system with or without sub speaker augmentation
- Suitable for speech and background music
- Flexible and easy-to install configurations (wall, ceiling, under balcony)
- U bracket included
- Combine with any ΣB or ΣJ Series high power sub speaker for extended low frequency, high quality music reproduction
- Powder coated grill
- Durable Polyurethane textured base paint
- 1 x NL4 conenctor included in packaging



System Specifications:

Construction	15mm Birch Plywood
Transducers	1 x 1" HF Compression Driver + 1 x 8" LF
Crossover	2.5kHz
Frequency Response (-3dB)	85Hz-19kHz
Rated Power	100W (RMS)
Sensitivity (1W @ 1m)	93dB
Rated Impedance	8Ω
Dispersion (H x V)	140° x 140°
Connector	1 x NL4
Dimensions (W x D x H)	258mm (10.2") x 247mm (9.7") x 408mm (16.1")
Packaging Dimensions (2 pieces/pack)	617mm (24.3") x 337mm (13.3") x 508mm (20")
Net Weight (2 pieces/pack)	16kg (35.2lb)
Gross Weight (2 pieces/pack)	19kg (41.8lb)

