

Product Description:

Portable and Installed PA loudspeakers used in applications including sound reinforcement and stage monitoring in Houses of Worship, Events, Clubs, Rehearsal Halls, Ballrooms. Σ Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High SPL and sensitivity
- 1 x 10" high power low frequency transducer
- 1 x 1.7" titanium diaphragm compression driver
- Passive configuration
- (55-100)° x 50° controlled coverage pattern
- 1 x NL4 connector
- Computer aided design to optimise frequency and phase response
- Multi purpose cabinet design for FOH or monitor use
- Suitable for use as a main system with or without sub speaker augmentation
- Integral 35mm pole mount receptacle for stand or vertical installation
- 6 x mounting points for permanent installation (wall, ceiling, under balcony)
- Combine with any ΣB or ΣJ Series high power sub speaker for extended low frequency, high quality music reproduction
- Powder coated grill
- Durable Polyurethane textured base paint
- 1 x NL4 conenctor included in packaging

**System Specifications:**

Construction	15mm Birch Plywood
Transducers	1 x 1.7" HF Compression Driver + 1 x 10" LF
Crossover	2.5kHz
Frequency Response (-3dB)	60Hz-20kHz
Rated Power	200W (RMS)
Sensitivity (1W @ 1m)	95dB
Rated Impedance	8Ω
Dispersion (H x V)	(55°-100°) x 50°
Connector	1 x NL4
Dimensions (W x D x H)	330mm (13") x 308mm (12.1") x 502mm (19.8")
Packaging Dimensions (1 piece/pack)	430mm (16.9") x 408mm (16.1") x 622mm (24.5")
Net Weight (1 piece/pack)	15kg (33lb)
Gross Weight (1 piece/pack)	18kg (39.6lb)

