

## Product Description:

Portable and installed PA loudspeakers used in applications including sound reinforcement in Houses of Worship, Events, Clubs, Rehearsal Halls and Ballrooms etc. The MU Active Series delivers extraordinary performance at unmatched value.

## Key Features and Benefits:

- High output SPL and sensitivity
- 1 x 12" high power low frequency transducer with 75mm voice coil
- Sensitivity 92dB, max SPL 123dB
- RMS 300W, peak 1200W
- Built-in power amplifier module
- Master volume control
- XLR input and output connectors
- Built in variable crossover 80Hz-250Hz high cut
- Phase switch
- Computer aided design to optimise frequency and phase response
- Cabinet designed for FOH use
- Suitable for use with any full range or mid/high speaker cabinets for extended low frequency, high quality music reproduction
- Integral 35mm pole receptacle for mounting full range or mid/high speaker cabinet
- Powder coated grill with foam backing
- Durable Polyurethane textured base paint



## System Specifications:

Construction	15mm Birch Plywood
Transducers	1 x 12" LF
Frequency Response (-3dB)	40Hz-250Hz
Rated Power	300W (RMS), 600W (Program), 1200W (Peak)
Amplifier Type	Class H
Sensitivity (1W @ 1m)	92dB
Maximum SPL (1W @ 1m)	118dB/124dB (Peak)
Rated Impedance	4Ω
Connector	1 x Combo 6.35/XLR Input, 1 x XLR Output
Power Supply	110V/220V
Dimensions (W x D x H)	460mm (18.1") x 452mm (17.8") x 370mm (14.6")
Packaging Dimensions (1 piece/pack)	550mm (21.7") x 550mm (21.7") x 470mm (18.5")
Net Weight (1 piece/pack)	22.5kg (49.5lb)
Gross Weight (1 piece/pack)	24.5kg (53.9lb)

