

Product Description:

Portable and installed PA loudspeakers used in applications including sound reinforcement in Houses of Worship, Events, Clubs, Rehearsal Halls and Ballrooms etc. The MU Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High output SPL and sensitivity
- 1 x 12" high power transducer with 75mm voice coil
- 1 x 3" compression driver
- 60° x 40° coverage pattern
- 2 x NL4 connectors
- Computer aided design to optimise frequency and phase response
- Cabinet design for FOH use
- Suitable for use as a main system with or without sub speaker augmentation
- Portable system (stand), or permanent installation (wall, ceiling, under balcony)
- Adjustable flying track on the top and bottom of the speaker
- Arrays with MU12B, MU12Ba, MU18B and MU18Ba high power sub speakers for extended low frequency, high quality music reproduction
- Powder coated grill with foam backing
- Durable Polyurethane textured base paint
- 1 x NL4 connector included in packaging



System Specifications:

Construction	15mm Birch Plywood
Transducers	1 x 3" HF Compression Driver + 1 x 12" LF
Crossover	1.8kHz
Frequency Response (-3dB)	55Hz-17kHz
Rated Power	400W (RMS), 800W (Program), 1600W (Peak)
Sensitivity (1W @ 1m)	97dB
Maximum SPL (1W @ 1m)	123dB/129dB (Peak)
Rated Impedance	8Ω
Dispersion (H x V)	60° x 40°
Connector	2 x NL4
Dimensions (W x D x H)	420mm (16.5") x 420mm (16.5") x 610mm (24")
Packaging Dimensions (1 piece/pack)	530mm (20.8") x 530mm (20.8") x 730mm (28.7")
Net Weight (1 piece/pack)	24kg (52.8lb)
Gross Weight (1 piece/pack)	26kg (57.2lb)

