

Product Description:

Portable and installed PA loudspeakers used in applications including sound reinforcement in Houses of Worship, Events, Clubs, Rehearsal Halls and Ballrooms etc. The MU Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High output SPL and sensitivity
- 1 x 18" high power low frequency transducer with 100mm voice coil
- 2 x NL4 connectors
- Sensitivity 97dB, max SPL 124dB
- Passive configuration
- RMS 500W, peak 2000W
- Computer aided design to optimise frequency and phase response
- Cabinet designed for FOH use
- Suitable for use with any full range or mid/high speaker cabinets for extended low frequency, high quality music reproduction
- Integral 35mm pole receptacle for mounting full range or mid/high speaker cabinet
- Powder coated grill with foam backing
- Durable Polyurethane textured base paint
- 1 x NL4 connector included in packaging



System Specifications:

Construction	18mm Birch Plywood
Transducers	1 x 18" LF
Frequency Response (-3dB)	40Hz-300Hz
Rated Power	500W (RMS), 1000W (Program), 2000W (Peak)
Sensitivity (1W @ 1m)	97dB
Maximum SPL (1W @ 1m)	124dB/130dB (Peak)
Rated Impedance	8Ω
Connector	2 x NL4
Dimensions (W x D x H)	600mm (23.6") x 640mm (25.2") x 550mm (21.7")
Packaging Dimensions (1 piece/pack)	750mm (29.5") x 710mm (28") x 670mm (26.4")
Net Weight (1 piece/pack)	38kg (83.6lb)
Gross Weight (1 piece/pack)	44kg (96.8lb)

