

Product Description:

Professional portable and installed plastic loudspeakers where high sound quality is required. Can be used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Events, Clubs, Rehearsal Halls etc. The S Series is suitable for music and vocal reproduction in demanding applications.

Key Features and Benefits:

- High output SPL and sensitivity
- 2 x 12" high power transducers
- Injection molded
- 2 x NL4 connector
- Cabinet design for FOH use
- Suitable for use to augment the main system
- Portable system (stand), or permanent installation (wall, ceiling)
- Powder coated grill with foam backing
- Available in black or white



System Specifications:

Construction	Plastic
Transducers	2 x 12" LF
Frequency Response (-3dB)	50Hz-1.8kHz
Rated Power	800W (RMS), 1600W (Program), 3200W (Peak)
Sensitivity (1W @ 1m)	99dB
Maximum SPL (1W @ 1m)	128dB/134dB (Peak)
Rated Impedance	4Ω
Connector	2 x NL4
Dimensions (W x D x H)	416mm (16.4") x 423mm (16.6") x 721mm (28.4")
Packaging Dimensions (1 piece/pack)	485mm (19.1") x 485mm (19.1") x 792mm (31.2")
Net Weight (1 piece/pack)	24.5kg (53.9lb)
Gross Weight (1 piece/pack)	28kg (61.6lb)

