

Product Description:

Professional portable and installed plastic loudspeakers where high sound quality is required. Can be used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Events, Clubs, Rehearsal Halls etc. The S Series is suitable for music and vocal reproduction in demanding applications.

Key Features and Benefits:

- High output SPL and sensitivity
- 2 x 4" high power transducers
- 1 x 1" diaphragm compression driver
- 120° x 120° controlled coverage pattern
- Injection molded
- 1 x NL4 connector
- Cabinet design for FOH use
- Suitable for use as a main system with or without sub speaker augmentation
- Portable system (stand), or permanent installation (wall, ceiling, under balcony)
- Powder coated grill with foam backing
- Comes with convenient mounting bracket
- Available with 70V/100V line transformer
- Available in black or white



System Specifications:

Construction	Plastic
Transducers	1 x 1" HF + 2 x 4" LF
Crossover	3kHz
Frequency Response (-3dB)	80Hz-20kHz
Rated Power	80W (RMS), 160W (Program), 320W (Peak)
Sensitivity (1W @ 1m)	92dB
Maximum SPL (1W @ 1m)	111dB/117dB (Peak)
Rated Impedance	4Ω
Dispersion (H x V)	120° x 120°
Connector	1 x NL4
Dimensions (W x D x H)	182mm (7.5") x 182mm (7.5") x 320mm (12.6")
Packaging Dimensions (1 piece/pack)	230mm (9.1") x 230mm (9.1") x 375mm (14.8")
Net Weight (1 piece/pack)	4.5kg (9.9lb)
Gross Weight (1 piece/pack)	5.5kg (12.1lb)

