

Product Description:

Portable and installed PA loudspeakers used in applications including sound reinforcement in Houses of Worship, Events, Clubs, Rehearsal Halls and Ballrooms etc. The T Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High output SPL and sensitivity
- 1 x 10" high power low frequency driver
- 1 x 1.3" compression driver
- 90° x 60° controlled coverage
- Computer aided Polyurethane plastic cabinet deign
- Cabinet design for FOH and monitor use (integrated monitor feet)
- SMART pole mount to include 5° tilt
- M8 rigging points for installation
- Powder coated grill
- Portable system or permanent installation



System Specifications:

Construction	Plastic
Transducers	1 x 1.3" HF Compression Driver + 1 x 10" LF
Crossover	1.8kHz
Frequency Response (-3dB)	50Hz-19kHz
Rated Power	200W
Maximum SPL (1W @ 1m)	113dB
Rated Impedance	8Ω
Dispersion (H x V)	90° x 60°
Connector	2 x NL4
Dimensions (W x D x H)	306mm x 238mm x 516mm
Packaging Dimensions (1 piece/pack)	355mm x 355mm x 602mm
Net Weight (1 piece/pack)	13.2kg
Gross Weight (1 piece/pack)	14.7kg
Warranty	3 years







