

Product Description:

Portable and installed PA loudspeakers used in applications including sound reinforcement in Houses of Worship, Events, Clubs, Rehearsal Halls and Ballrooms etc. The T Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High output SPL and sensitivity
- 1 x 12" high power low frequency driver
- 1 x 1.7" compression driver
- 90° x 60° controlled coverage
- Computer aided Polyurethane plastic cabinet design
- Cabinet design for FOH and monitor use (integrated monitor feet)
- SMART pole mount to include 5° tilt
- M8 rigging points for installation
- Powder coated grill
- Portable system or permanent installation



System Specifications:

Construction	Plastic
Transducers	1 x 1.7" HF Compression Driver + 1 x 12" LF
Crossover	1.8kHz
Frequency Response (-3dB)	50Hz-19kHz
Rated Power	500W
Maximum SPL (1W @ 1m)	115dB
Rated Impedance	8Ω
Dispersion (H x V)	90° x 60°
Connector	2 x NL4
Dimensions (W x D x H)	368mm x 349mm x 630mm
Packaging Dimensions (1 piece/pack)	420mm x 420mm x 720mm
Net Weight (1 piece/pack)	20kg
Gross Weight (1 piece/pack)	22kg
Warranty	3 years

