



Product Description:

Installed line array column loudspeakers used in applications including sound reinforcement for Houses of Worship, Events, Theme Parks, Transit Terminals and Shopping Malls etc. The T Series delivers extraordinary performance where high speech intelligibility and natural sounding music is required at unmatched value.

Key Features and Benefits:

- Vertical line array of 6 x 4" full range transducers
- High fidelity sound
- Passive configuration
- 180° x 30° controlled coverage pattern
- Designed for high speech intelligibility and natural sounding music
- Suitable for use as a main system with or without sub speaker augmentation
- Quick install U bracket included with multiple mounting points provided
- Permanent installation (wall, ceiling, under balcony) or Portable system (stand adaptor included)
- Powder coated grill
- Durable Polyurethane textured base paint
- Available in either black or white
- 1 x NL4 conenctor included in packaging
- Optional 100/70V 100W transformer
- Optional processing recommended - can be used without
- Patents pending for central diffuser plate



System Specifications:

Construction	15mm Birch Plywood
Transducers	6 x 4"
Frequency Response (-3dB)	90Hz-16kHz
Rated Power	180W (RMS), 360W (Program), 720W (Peak)
Sensitivity (1W @ 1m)	92dB
Maximum SPL (1W @ 1m)	115dB/121dB (Peak)
Rated Impedance	8Ω
Dispersion (H x V)	180° x 25°
Connector	Screw Terminal and 1 x NL4
Dimensions (W x D x H)	135mm (5.3") x 169mm (6.7") x 800mm (31.5")
Packaging Dimensions (1 piece/pack)	240mm (9.5") x 205mm (8.1") x 900mm (35.4")
Net Weight (1 piece/pack)	9kg (19.8lb)
Gross Weight (1 piece/pack)	10kg (22lb)

