

Product Description:

Portable and installed PA loudspeakers used in applications including sound reinforcement for Bands, DJ's, Houses of Worship, Events, Clubs, Rehearsal Halls and Ballrooms etc. The TW Powered Series delivers extraordinary performance at unmatched value.

Key Features and Benefits:

- High output SPL and sensitivity
- Two 18" high power low frequency drivers
- Built-in 4500W Class D power amplifier module
- High output SPL and sensitivity
- Neutrik PowerCon input (15amp) and output power supply connectors
- High cut control
- XLR Line input and output
- Phase selector switch
- Volume control
- Computer aided design to optimise frequency and phase response
- Suitable for use with any full range or mid/high speaker cabinets for extended low frequency
- Powered coated grill with foam backing
- Durable Polyurethane textured base paint
- Portable system or for permanent installation (floor only)



System Specifications:

Construction	18mm Plywood
Transducers	2 x 18" LF
Frequency Response (-3dB)	40Hz-400Hz
Rated Power	4500W (RMS)
Amplifier Type	Class D
Maximum SPL (1W @ 1m)	132/138dB (Peak)
Input Impedance	Balanced 20kΩ, Unbalanced 2kΩ
Rated Impedance	4Ω
Connector	1 x XLR (Input), 1 x XLR (Output)
Power Supply	220V-240V
Dimensions (W x D x H)	567mm x 768mm x 1075mm
Packaging Dimensions (1 piece/pack)	685mm x 895mm x 1185mm
Net Weight (1 piece/pack)	86kg
Gross Weight (1 piece/pack)	91kg
Warranty	3 Years

